TECHNICAL SPECIFICATIONS



PASSION™ 8x42HD



PASSION™ 10x42HI



PASSION™ 8.5x50H



PASSION™ 10x50H



PASSION™ 12,5x50HE

Prism type:		Schmidt-Pechan	Schmidt-Pechan	Schmidt-Pechan	Schmidt-Pechan	Schmidt-Pechan
Magnification:		8x	10x	8,5x	10x	12,5x
Field of view (FOV) ft at 1000y:		375	336	315	309	286
Field of view (FOV) m at 1000m:		125	112	105	103	92
Objective diameter (mm):	Effective diameter	42	42	50	50	50
Ocular diameter (mm):	Effective diameter	42,2	42,2	42,2	42,2	42,2
Exit pupil diameter (mm):	Measurement of the pupilary ocular beam	5,25	4,2	5,88	5	4
Eye Relief (inches):	From the last optical surface	0,77	0,67	0,67	0,67	0,67
Eye Relief (mm):	From the last optical surface	19,5	17	17	17	17
Housing:	Main body and hinge	magnesium	magnesium	magnesium	magnesium	magnesium
Close focus (feet):	Shortest focal distance	6,5	6,5	9,8	9,2	8,2
Close focus (meters):	Shortest focal distance	2	2	3	2,8	2,5
Interpupilary Distance (IPD):	Center pupil to center pupil measurement	57-75	57-75	58-76	58-76	58-76
Dioptric compensation range:		-2.5, +2.5	-2.5, +2.5	-2.5, +2.5	-2.5, +2.5	-2.5, +2.5
Waterproof:	Mbars	300	300	300	300	300
Transmission Daylight:	ISO 14490-5:2005	91%	91%	91%	91%	91%
Height (inches):	Without covers	2,2	2,2	2,5	2,5	2,5
Height (mm):	Without covers	56	56	64	64	64
Weight (ounces):	Without covers	29,9	30,3	33,5	33,8	34,2
Weight (grams):	Without covers	850	860	950	960	970
Length (inches):	At outside diameter	6,1	6,1	6,9	6,9	6,9
Length (mm):	At outside diameter	156	156	175	175	175
Width (inches):	Fully extended	5,1	5,1	5,3	5,3	5,3
Width (mm):	Fully extended	130	130	135	135	135
Accessories inluded		instruction manual, cleaning cloth, hard				
with this purchase:		case, neoprene neck strap, hard case strap,				
		objective covers, ocular covers				