

TECHNICAL SPECIFICATIONS



PASSION™ 5x 1-5x24i



PASSION™ 5x 3,5-18x56i

Magnification:	.	1x - 5x	3,5 - 18x
Field of view (FOV) ft at 100y:	.	110 - 17,7	.
Field of view (FOV) m at 100m:	.	37 - 6	.
Objective diameter (mm):	Effective diameter	24	56
Exit pupil diameter (mm):	Measurement of the pupillary ocular beam	12,5 - 4	.
Eye Relief (inches):	From the last optical surface	3,54	3,54
Eye Relief (mm):	From the last optical surface	90	90
cm travel value per click at 100m:	1 Click = x/100m	1	1
Elevation range total (cm at 100m):	100m	300	.
Windage range total (cm at 100):	100m	200	.
Parallax compensation:	Parallax free at x distance	100 m	sidefocus
Transmission Daylight:	ISO 14490-5:2005	90%	90%
Height (inches):	Without covers	2	.
Height (mm):	Without covers	53	.
Width (inches):	Fully extended	2,7	.
Width (mm):	Fully extended	69,5	.
Length (inches):	At outside diameter	10,6	.
Length (mm):	At outside diameter	270	.
Tube diameter (mm):	Width of main tube	30	30
Weight (ounces):	Without covers	19,4	.
Weight (grams):	Without covers	550	.
Mechanical outer diameter (objective mm):	Obejctive end of scope	30	.
Mechanical outer diameter (ocular mm):	Ocular end of scope	43,5	.
Recticle Option:	.	G4i (German #4 illuminated)	G4i (German #4 illuminated)
Accessories included with this purchase:	.	instruction manual, cleaning cloth, bikini scope cover, battery CR2032	instruction manual, cleaning cloth, bikini scope cover, battery CR2032

